



# Tampacure TPC

## System Maracolor/Tampacolor:

	920 Lemon
	922 Light Yellow
	924 Medium Yellow
	926 Orange
	930 Vermilion
	932 Scarlet Red
	934 Carmine Red
	936 Magenta
	950 Violet
	952 Ultramarine Blue
	954 Medium Blue
	956 Brilliant Blue
	960 Blueish Green
	962 Grass Green
	940 Brown
	970 White
	980 Black

## 4-Colour Process Shades:

	429 Process-Yellow
	439 Process-Red
	459 Process-Blue
	489 Process-Black

## Further Shades:

	170 Opaque White
	180 Opaque Black
	409 Transparent Mass
	910 Overprint Varnish

## High-opaque Shades:

	122 Light Yellow
	130 Vermilion
	132 Scarlet Red
	162 Grass Green



## Tampacure TPC

### Informacija o proizvodu

Stepen sjaja	visoki sjaj
Sušenje	brzo
Vrsta sušenja	UV sušenje
Sistem boja	1 ili 2-komp.
Otpornost	hemijska sredstva
Specijalne karakteristike	visoka otpornost

### Dodaci

Razređivač	TPV
Brzi razređivač	TPV 2
Spori razređivač	-
Usporivač	-
Usporivač pasta	-
Učvršćivač	-
Brzi učvršćivač	H 2, 5%
Učvršćivač koji reaguje na toplotu	-
Antistatik pasta	AP
Pasta za deko- vanje	OP 170
Lak nakon štampanja, vezivo za bronzu	TPC 910
Transparentna baza	TPC 409
Mat pasta	-
Mat puder	MP
Dodatak za izjednačavanje -nivelisanje boje	ES
Prajmer za PP	P 2
Čistač	UR 3

### Podloge

ABS	●
Klirit (PMMA)	○
Eloksirani alu- minijum	
Termostabilna plastika	○*
Staklo, keramika	
Lakirane površine	●*
Melaminska smola	
Metal	
Papir, karton	
Poliacetat (POM)	
Poliamid (PA)	●*
Polikarbonat (PC)	●
Poliester (PET)	
PE, tretirani	●*
PP tretirani	●*
PP netretirani	
Polistiren (PS)	○
Poliuretani, tvrdi	
PVC, tvrdi	●
PVC, meki	
Termoplastični elastomer (TPE)	
Razni tipovi gume	
Podloge meke na dodir	

### Legenda

● - odgovara      ○ - delimično odgovara      \* - sa učvršćivačem      \* - ne odgovara mašinskom pranju

← - sa posttretmanom plamenovanja ili posttretman sa toplim vazduhom (3-4 sec. na 300-400°C).

## Tampacure TPC

- UV-zaštitna
- Visoko otporna
- Višenamenska

UV-zaštitna, sa visokim sjajem boja Tampacure TPC je najpogodnija boja za najotpornije materijale kod tehničkih proizvoda i proizvoda za kućnu upotrebu. Koristi se na ABS-u, predtretiranom polietilenu i polipropilenu podjednako dobro kao i na lakiranim površinama. Brzi proces UV-zaštite naročito je važan ako morate da rukujete sa tek odštampanim delovima.